Message formats for Article Transactions

EA -- Enter Article

Note: Entry formats are positional. All fields must be accounted for with a period even if the field is not mandatory. Field prefixes are not permitted. A "Cond. Set" means that if one of the fields is entered all of the fields in the set are required. A "One of Set" means that at least one of the fields in the set is required.

Message Structure:

{ssss}TCC#\$1N01rrrr ccccccccc.EA-c.<ori>

Such That:

-C		4 4 1-10	Optional	Mnemonic of Sending Device Mnemonic of Receiving Device Control Field; Used for routing within the interface system Message Key Qualifier -P Hold for Latents Agency's FBI assigned Originating Agency Identifier
		,		Agency 3 FBI ussigned originating Agency Identifier
Follow	ea By:			
. <t< td=""><td>typ></td><td>4-7</td><td>Required</td><td>Type. Alpha characters only; no spaces allowed. If the first character is other than "Y", then code as defined in the NCIC 2000 Code Manual.</td></t<>	typ>	4-7	Required	Type. Alpha characters only; no spaces allowed. If the first character is other than "Y", then code as defined in the NCIC 2000 Code Manual.
.<5	ser>	1-20	One of Set (1)	Serial Number. Alphanumeric. Cannot be a single zero only, a run of zeros only, a single alphabetic only, or a run of alphabetics only. Cannot be identical to the OAN.
. < k	bra>	2-6	Required	Brand. Alphanumeric; hyphens are permitted. Cannot be all X, Y, Z, L, UNK, UNKN, or NONE.
. <r< td=""><td>mod></td><td>1-9</td><td></td><td>Model. Use last 9 characters of actual model number. May be alphanumeric, spaces are allowed.</td></r<>	mod>	1-9		Model. Use last 9 characters of actual model number. May be alphanumeric, spaces are allowed.
.<0	oan>	1-20	One of Set (1)	Owner Applied Number. Alphanumeric. Cannot be a single zero only, a run of zeros only, a single alphabetic only, or a run of repeated alphabetics. Cannot be identical to the SER.
.<0	dot>	8	Required	Date of Theft in YYYYMMDD format.
.<0	oca>	1-20	Required	Originating Case Number. The only valid special characters are the hyphen and the space. Other exceptions are described in the NCIC 2000 Operating Manual.
.<1	lki>	9	Cond. Set (1)	Linkage Agency Identifier. Must be a valid NCIC-assigned ORI.
.<1	lka>	1-20	Cond. Set (1)	Linkage Case Number. The only valid special characters are the hyphen and the space. Other exceptions are described in the NCIC 2000 Operating Manual.
. <r< td=""><td>mis></td><td>1-200</td><td></td><td>Miscellaneous. Free text.</td></r<>	mis>	1-200		Miscellaneous. Free text.
. <r< td=""><td>noa></td><td>1</td><td></td><td>Notify Originating Agency. Must be either Y or N.</td></r<>	noa>	1		Notify Originating Agency. Must be either Y or N.
.<	lot>	1-20		Lot number. Free text.
. <h< td=""><td>hmc></td><td>1-25</td><td></td><td>Hazardous Materials Container. Free text.</td></h<>	hmc>	1-25		Hazardous Materials Container. Free text.
. <p< td=""><td>pli></td><td>1</td><td></td><td>Partial Lot Indicator. Must be P (Partial) or C (Complete).</td></p<>	pli>	1		Partial Lot Indicator. Must be P (Partial) or C (Complete).
.<١	unn>	4		United Nations Number. Entry permitted only when first character of TYP is T. Must be numeric code as maintained in the NLETS HazMat file.

MA -- Modify Article

Note: To Delete a non-Mandatory field, send the MFC (prefix) with no data. Once modified, the record must adhere to the entry rules.

Message Structure:

{ssss}TCC#\$1N01rrrr ccccccccc.MA.<ori>

Such That:

ssss 4 Mnemonic of Sending Device rrrr 4 Mnemonic of Receiving Device

cccccccc 1-10 Control Field; Used for routing within the interface system .<ori> 9 Agency's FBI assigned Originating Agency Identifier

Followed By (Selection Criteria):

.NIC/<nic> 10 NIC number. Number assigned by NCIC upon record entry.

Followed by one of the following:

.SER/<ser> 1-20 Serial Number. Alphanumeric. Cannot be a single zero only, a run of zeros only, a single

alphabetic only, or a run of alphabetics only. Cannot be identical to the OAN.

.OCA/<oca> 1-20 Originating Case Number. The only valid special characters are the hyphen and the space.

Other exceptions are described in the NCIC 2000 Operating Manual.

.OAN/<oan> 1-20 Owner Applied Number. Alphanumeric. Cannot be a single zero only, a run of zeros only, a

single alphabetic only, or a run of repeated alphabetics. Cannot be identical to the SER.

Followed by at least one of the following:

.MKE/ <mke></mke>	2-4	Message Key. Permits the change of the Message Key Qualifier.
ORI/ <ori></ori>	9	Originating Agency Identifier of the record's owner.

.TYP/<typ> 4-7 Type. Alpha characters only; no spaces allowed. If the first character is other than "Y", then

code as defined in the NCIC 2000 Code Manual.

.SER/<ser> 1-20 Serial Number. Alphanumeric. Cannot be a single zero only, a run of zeros only, a single

alphabetic only, or a run of alphabetics only. Cannot be identical to the OAN.

.BRA/<bra> 2-6 Brand. Alphanumeric; hyphens are permitted. Cannot be all X, Y, Z, L, UNK, UNKN, or NONE.

.MOD/<mod> 1-9 Model. Use last 9 characters of actual model number. May be alphanumeric, spaces are

allowed.

.OAN/<oan> 1-20 Owner Applied Number. Alphanumeric. Cannot be a single zero only, a run of zeros

only, a single alphabetic only, or a run of repeated alphabetics. Cannot be identical to the SER.

.DOT/<dot> 8 Date of Theft in YYYYMMDD format.

.OCA/<oca> 1-20 Originating Case Number. The only valid special characters are the hyphen and the space.

Other exceptions are described in the NCIC 2000 Operating Manual.

.LKI/<lki> 9 Linkage Agency Identifier. Must be a valid NCIC-assigned ORI.

.LKA/<lka> 1-20 Linkage Case Number. The only valid special characters are the hyphen and the space. Other

exceptions are described in the NCIC 2000 Operating Manual.

.MIS/<mis> 1-200 Miscellaneous. Free text.

.NOA/<noa> 1 Notify Originating Agency. Must be either Y or N.

.LOT/<lot> 1-20 Lot number. Free text.

.HMC/<hmc> 1-25 Hazardous Materials Container. Free text.

.PLI/<pli> 1 Partial Lot Indicator. Must be P (Partial) or C (Complete).

.UNN/<unn> 4 United Nations Number. Entry permitted only when first character of TYP is T. Must be

numeric code as maintained in the NLETS HazMat file.

XA -- Cancel Article

Message Structure:

{ssss}TCC#\$1N01rrrr ccccccccc.XA.<ori>

Such That:

ssss 4 Mnemonic of Sending Device rrrr 4 Mnemonic of Receiving Device

cccccccc 1-10 Control Field; Used for routing within the interface system .<ori> 9 Agency's FBI assigned Originating Agency Identifier

Followed By (Selection Criteria):

.NIC/<nic> 10 NIC number. Number assigned by NCIC upon record entry.

Followed by one of the following:

.SER/<ser> 1-20 Serial Number. Alphanumeric. Cannot be a single zero only, a run of zeros only, a single

alphabetic only, or a run of alphabetics only.

.OCA/<oca> 1-20 Originating Case Number. The only valid special characters are the hyphen and the space.

Other exceptions are described in the NCIC 2000 Operating Manual.

.OAN/<oan> 1-20 Owner Applied Number. Alphanumeric. Cannot be a single zero only, a run of zeros only, a

single alphabetic only, or a run of repeated alphabetics.

Followed By:

.<doc> 8 Date of Cancel in YYYYMMDD format.

Followed Optionally By:

.<rpp> 10-21 Reason for Property Record Removal.

ZA -- Administrative Query Article

Message Structure:

{ssss}TCC#\$1N01rrrr cccccccc.ZA.<ori>

Such That:							
	SSSS	4	Mnemonic of Sending Device				
	rrrr	4	Mnemonic of Receiving Device				
	cccccccc	1-10	Control Field; Used for Routing within the Interface Agency's FBI assigned Originating Agency Identifier				
	. <ori></ori>	9					
Fol	lowed By:						
	.NIC/ <nic></nic>	10	NIC number. Number assigned by NCIC upon record entry.				
Or							
	.TYP/ <typ></typ>	4-7	Type. Alpha characters only; no spaces allowed. If the first character is other than "Y", then code as defined in the NCIC 2000 Code Manual.				
	.SER/ <ser></ser>	1-20	Serial Number. Alphanumeric. Cannot be a single zero only, a run of zeros only, a single alphabetic only, or a run of alphabetics only.				
and	and optionally						
	, <oan></oan>	1-20	Owner Applied Number. Alphanumeric. Cannot be a single zero only, a run of zeros only, a single alphabetic only, or a run of repeated alphabetics.				
	.RSH/ <rsh></rsh>	1	Related Search Hit. Must be either Y or N.				
Or							
	.TYP/ <typ></typ>	4-7	Type. Alpha characters only; no spaces allowed. If the first character is other than "Y", then code as defined in the NCIC 2000 Code Manual.				
	.SER/ <oan></oan>	1-20	Owner Applied Number. Alphanumeric. Cannot be a single zero only, a run of zeros only, a single alphabetic only, or a run of repeated alphabetics.				
and	and optionally						
	.RSH/ <rsh></rsh>	1	Related Search Hit. Must be either Y or N.				

QA -- Query Article

Message Structure:

{ssss}TCC#\$1N01rrrr ccccccccc.QA.<ori>

S		_	h		TI	٠,	2	+
. > 1	•	(rı	١.,	ır	17	11	1

ssss 4 Mnemonic of Sending Device rrrr 4 Mnemonic of Receiving Device

cccccccc 1-10 Control Field; Used for Routing within the Interface .<ori> 9 Agency's FBI assigned Originating Agency Identifier

Followed By:

.NIC/<nic> 10 NIC number. Number assigned by NCIC upon record entry.

Or

.TYP/<typ> 4-7 Type. Alpha characters only; no spaces allowed. If the first character is other than "Y", then

code as defined in the NCIC 2000 Code Manual.

.SER/<ser> 1-20 Serial Number. Alphanumeric. Cannot be a single zero only, a run of zeros only, a single

alphabetic only, or a run of alphabetics only.

and optionally

,<oan> 1-20 Owner Applied Number. Alphanumeric. Cannot be a single zero only, a run of zeros only, a

single alphabetic only, or a run of repeated alphabetics.

.RSH/<rsh> 1 Related Search Hit. Must be either Y or N.

Or

.TYP/<typ> 4-7 Type. Alpha characters only; no spaces allowed. If the first character is other than "Y", then

code as defined in the NCIC 2000 Code Manual.

.SER/<oan> 1-20 Owner Applied Number. Alphanumeric. Cannot be a single zero only, a run of zeros only, a

single alphabetic only, or a run of repeated alphabetics.

and optionally

.RSH/<rsh> 1 Related Search Hit. Must be either Y or N.

LA -- Locate Article

Message Structure:

{ssss}TCC#\$1N01rrrr ccccccccc.LA.<ori>

Such That:

ssss 4 Mnemonic of Sending Device rrrr 4 Mnemonic of Receiving Device

cccccccc 1-10 Control Field; Used for Routing within the Interface .<ori> 9 Agency's FBI assigned Originating Agency Identifier

Followed By (Selection Criteria):

.NIC/<nic> 10 NIC number. Number assigned by NCIC upon record entry.

Followed by one of the following:

.SER/<ser> 1-20 Serial Number. Alphanumeric. Cannot be a single zero only, a run of zeros only, a single

alphabetic only, or a run of alphabetics only.

.OCA/<oca> 1-20 Originating Case Number. The only valid special characters are the hyphen and the space.

Other exceptions are described in the NCIC 2000 Operating Manual.

.OAN/<oan> 1-20 Owner Applied Number. Alphanumeric. Cannot be a single zero only, a run of zeros only, a

single alphabetic only, or a run of repeated alphabetics.

Followed By:

.<dor> 8 Date of Recovery in YYYYMMDD format.

.<rca> 1-20 OCA of Recovering Agency.

Followed Optionally by:

. <rpp></rpp>	10-21	Reason for Property Record Removal. Must be a valid NCIC-assigned code. See the NCIC 2000 Operating Manual.				
. <npa></npa>	1-3	Number of Persons Apprehended. See the NCIC 2000 Operating Manual for specific coding instructions.				
. <npf></npf>	1-20	Number of Missing Persons Found. See the NCIC 2000 Operating Manual for specific coding instructions.				
. <vnp></vnp>	1-8	Value of Recovered Property See the NCIC 2000 Operating Manual for specific coding instructions.				
. <vor></vor>	1-8	Value of Other Recovered Property. See the NCIC 2000 Operating Manual for specific coding instructions.				
. <vrc></vrc>	1-8	Value of Recovered Contraband. See the NCIC 2000 Operating Manual for specific coding instructions.				

CA -- Clear Article

Message Structure:

{ssss}TCC#\$1N01rrrr ccccccccc.CA.<ori>

Such That:

ssss 4 Mnemonic of Sending Device rrrr 4 Mnemonic of Receiving Device

ccccccccc 1-10 Control Field; Used for routing within the interface system .<ori> 9 Agency's FBI assigned Originating Agency Identifier

Followed By (Selection Criteria):

.NIC/<nic> 10 NIC number. Number assigned by NCIC upon record entry.

Followed by only one of the following:

.SER/<ser> 1-20 Serial Number. Alphanumeric. Cannot be a single zero only, a run of zeros only, a single

alphabetic only, or a run of alphabetics only.

.OCA/<oca> 1-20 Originating Case Number. The only valid special characters are the hyphen and the space.

Other exceptions are described in the NCIC 2000 Operating Manual.

.OAN/<oan> 1-20 Owner Applied Number. Alphanumeric. Cannot be a single zero only, a run of zeros only, a

single alphabetic only, or a run of repeated alphabetics.

Followed by:

.<dcl> 8 Date of Clear in YYYYMMDD format.

.<rri> 9 ORI of Recovering Agency. .<rca> 1-20 OCA of Recovering Agency.

Followed Optionally By:

.<rpp> 10-21 Reason for Property Record Removal. Must be a valid NCIC-assigned code. See the NCIC 2000

Operating Manual.

.<npa> 1-3 Number of Persons Apprehended. See the NCIC 2000 Operating Manual for

specific coding instructions.

.<npf> 1-20 Number of Missing Persons Found. See the NCIC 2000 Operating Manual for

specific coding instructions.

.<vnp> 1-8 Value of Recovered Property. See the NCIC 2000 Operating Manual for specific

coding instructions.

.<vor> 1-8 Value of Other Recovered Property. See the NCIC 2000 Operating Manual for

specific coding instructions.

.<vrc> 1-8 Value of Recovered Contraband. See the NCIC 2000 Operating Manual for

specific coding instructions.