Message formats for Vehicle Transactions

EV -- Enter Vehicle

Note: Entry formats are positional. All fields must be accounted for with a period even if the field is not mandatory. Field prefixes are not permitted. A "Cond. Set" means that if one of the fields is entered all of the fields in the set are required. A "One of Set" means that at least one of the fields in the set is required.

Message Structure:

{ssss}TCC#\$1N01rrrr ccccccccc.EV-c.<ori>

Such That:

-C	r ccccccc ori>	4 4 1-10	Optional	Mnemonic of Sending Device Mnemonic of Receiving Device Control Field; Used for routing within the interface system Message Key Qualifier -P Hold for Latents -A Occupant(s) Armed -F Hold for Latents/Occupant(s) Armed Agency's FBI assigned Originating Agency Identifier
	lic>	1-10	One of Set (1) & Cond. Set (1)	License Plate Number. If the license plate number exceeds ten characters, only the last ten characters should be used. If the LIC is UNK, UNKN or UNKNOWN, contact NCIC CJIS Division for assistance. Paper Dealer Plates are not allowed. LIC or VIN is Required.
. < l	lis>	2	Cond. Set (1)	License Plate State. Code as defined in the NCIC 2000 Code Manual.
.<1	liy>	2 or 4	Cond. Set (1)	License Plate Year. Must represent the year the license plate expires (YYYY) or the alphabetics 'NX' to represent a nonexpiring license plate.
. < l	lit>	2	Cond. Set (1)	License Plate Type. Code as defined in the NCIC 2000 Code Manual.
.<\	vin>	1-20	One of Set (1)	Vehicle Identification Number. Alphanumeric. Single zero only, run of zeros only, single alphabetic only, all alphabetics only, or spaces cannot be used. If the Vehicle in question is a trailer and has a non standard VIN, enter SVIN in the first 4 characters of the miscellaneous field to force entry.
.<\	vyr>	4	Required	Vehicle Year. Must represent the model year during which the vehicle was manufactured (YYYY). Must be less than or equal to the current year plus one.
.<\	vma>	2-24	Required	Vehicle Make. Code as defined in the NCIC 2000 Code Manual.
.<\	vmo>	2-3		Vehicle Model. Code as defined in the NCIC 2000 Code Manual.
.<\	vst>	2	Required	Vehicle Style. Code as defined in the NCIC 2000 Code Manual.
.<\	VCO>	3 or 7		Vehicle Color. Code as defined in the NCIC 2000 Code Manual.
.<0	dot>	8	Required	Date of Theft in YYYYMMDD format.
.<0	oca>	1-20	Required	Originating Case Number. The only valid special characters are the hyphen and the space. Other exceptions are described in the NCIC 2000 Operating Manual.
.<1	lki>	9	Cond. Set (2)	Linkage Agency Identifier. Must be a valid NCIC-assigned ORI.
.<	lka>	1-20	Cond. Set (2)	Linkage Case Number. The only valid special characters are the hyphen and the space. Other exceptions are described in the NCIC 2000 Operating Manual.
. <r< td=""><td>mis></td><td>1-200</td><td></td><td>Miscellaneous. Free text.</td></r<>	mis>	1-200		Miscellaneous. Free text.
. <r< td=""><td>noa></td><td>1</td><td></td><td>Notify Originating Agency. Must be either Y or N.</td></r<>	noa>	1		Notify Originating Agency. Must be either Y or N.
.<(oan>	1-20		Owner Applied Number. Alphanumeric. Cannot be a single zero only, a run of zeros only, a single alphabetic only, or a run of alphabetics only. Motor or engine numbers allowed. Model Numbers not allowed. Only allowed if VIN is used.

MV -- Modify Vehicle

Note: To Delete a non-Mandatory field, send the MFC (prefix) with no data. Once modified, the record must adhere to the entry rules.

Message Structure:

{ssss}TCC#\$1N01rrrr ccccccccc.MV.<ori>

Such That:

ssss 4 Mnemonic of Sending Device rrrr 4 Mnemonic of Receiving Device

cccccccc 1-10 Control Field; Used for routing within the interface system .<ori> 9 Agency's FBI assigned Originating Agency Identifier

Followed by one of the following:

.LIC/
1-10
License Plate Number. If the license plate number exceeds ten characters, only the last ten characters should be used.

.OCA/<oca> 1-20 Originating Case Number. The only valid special characters are the hyphen and the space.

Other exceptions are described in the NCIC 2000 Operating Manual.

OR

.LKI/<lki>

.LKA/<lka>

9

1-20

.VIN/<vin> 1-20 Vehicle Identification Number. Alphanumeric. Single zero only, run of zeros only, single

alphabetic only, all alphabetics only, or spaces cannot be used.

.OCA/<oca> 1-20 Originating Case Number. The only valid special characters are the hyphen and the space.

Other exceptions are described in the NCIC 2000 Operating Manual.

Followed by at least one of the following:

//(owed by at i	east one or the rollov	ving.
	.MKE/ <mke></mke>	2-4	Message Key. Permits the change of the Message Key Qualifier.
	.ORI/ <ori></ori>	9	Originating Agency Identifier of the record's owner.
	.VLN/ <vln></vln>	3-30	Validator Name.
	.LIC/ <lic></lic>	1-10	License Plate Number. If the license plate number exceeds ten characters, only the last ten characters should be used. If the LIC is UNK, UNKN or UNKNOWN, contact NCIC CJIS Division for assistance. Paper Dealer Plates are not allowed. LIC or VIN is Required.
	.LIS/ <lis></lis>	2	License Plate State. Code as defined in the NCIC 2000 Code Manual.
	.LIY/ <liy></liy>	2 or 4	License Plate Year. Must represent the year the license plate expires (YYYY) or the alphabetics 'NX' to represent a nonexpiring license plate.
	.LIT/ <lit></lit>	2	License Plate Type. Code as defined in the NCIC 2000 Code Manual.
	.VIN/ <vin></vin>	1-20	Vehicle Identification Number. Alphanumeric. Single zero only, run of zeros only, single alphabetic only, all alphabetics only, or spaces cannot be used. If the Vehicle in question is a trailer and has a non standard VIN, enter SVIN in the first 4 characters of the miscellaneous field to force entry.
	.VYR/ <vyr></vyr>	4	Vehicle Year. Must represent the model year during which the vehicle was manufactured (YYYY). Must be less than or equal to the current year plus one.
	.VMA/ <vma></vma>	2-24	Vehicle Make. Code as defined in the NCIC 2000 Code Manual.
	.VMO/ <vmo></vmo>	2-3	Vehicle Model. Code as defined in the NCIC 2000 Code Manual.
	.VST/ <vst></vst>	2	Vehicle Style. Code as defined in the NCIC 2000 Code Manual.
	.VCO/ <vco></vco>	3 or 7	Vehicle Color. Code as defined in the NCIC 2000 Code Manual.
	.DOT/ <dot></dot>	8	Date of Theft in YYYYMMDD format.
	.OCA/ <oca></oca>	1-20	Originating Case Number. The only valid special characters are the hyphen and the space. Other exceptions are described in the NCIC 2000 Operating Manual.

Linkage Case Number. The only valid special characters are the hyphen and the space. Other

Linkage case number. The only valid special characters are the hypneri and the space. Other

exceptions are described in the NCIC 2000 Operating Manual.

Linkage Agency Identifier. Must be a valid NCIC-assigned ORI.

.MIS/<mis> 1-200 Miscellaneous. Free text.

.NOA/<noa> 1 Notify Originating Agency. Must be either Y or N.

.OAN/<oan> 1-20 Owner Applied Number. Alphanumeric. Cannot be a single zero only, a run of zeros only, a

single alphabetic only, or a run of alphabetics only. Motor or engine numbers allowed. Model

Numbers not allowed. Only allowed if VIN is used.

XV -- Cancel Vehicle

Message Structure:

{ssss}TCC#\$1N01rrrr ccccccccc.XV.<ori>

Such That:

ssss 4 Mnemonic of Sending Device rrrr 4 Mnemonic of Receiving Device

cccccccc 1-10 Control Field; Used for routing within the interface system .<ori> 9 Agency's FBI assigned Originating Agency Identifier

Followed by one of the following:

.LIC/
.LIC/
1-10
License Plate Number. If the license plate number exceeds ten characters, only the last ten

characters should be used.

.OCA/<oca> 1-20 Originating Case Number. The only valid special characters are the hyphen and the space.

Other exceptions are described in the NCIC 2000 Operating Manual.

OR

.VIN/<vin> 1-20 Vehicle Identification Number. Alphanumeric. Single zero only, run of zeros only, single

alphabetic only, all alphabetics only, or spaces cannot be used.

.OCA/<oca> 1-20 Originating Case Number. The only valid special characters are the hyphen and the space. c

Other exceptions are described in the NCIC 2000 Operating Manual.

Followed By:

.<doc> 8 Date of Cancel in YYYYMMDD format.

Followed Optionally By:

.<rpp> 10-21 Reason for Property Record Removal.

ZV -- Administrative Query Vehicle

Message Structure:

{ssss}TCC#\$1N01rrrr ccccccccc.ZV-c.<ori>

Such	That:
S	SSS

ssss 4 Mnemonic of Sending Device rrrr 4 Mnemonic of Receiving Device

cccccccc 1-10 Control Field; Used for Routing within the Interface

-c -T TCIC Only

.<ori> 9 Agency's FBI assigned Originating Agency Identifier

Followed By:

.NIC/<nic> 10 NIC number. Number assigned by NCIC upon record entry.

Or

.LIC/
 License Plate Number. If the license plate number exceeds ten characters, only the last ten

characters should be used.

Or / And

.VIN/<vin> 1-20 Vehicle Identification Number. Alphanumeric. Single zero only, run of zeros only, single

alphabetic only, all alphabetics only, or spaces cannot be used.

And optionally

.LIS/
 2 License Plate State. Code as defined in the NCIC 2000 Code Manual.

.VMA/<vma> 2-24 Vehicle Make. Code as defined in the NCIC 2000 Code Manual.

.RSH/<rsh> 1 Related Search Hit. Must be either Y or N.

.HDN/<hdn> 1 H.E.A.T. Inquiry Indicator. Indicates if this transaction is a result of a stop due to the

presence of a H.E.A.T. Decal. Must be either Y or N.

QV -- Query Vehicle

Message Structure:

{ssss}TCC#\$1N01rrrr ccccccccc.QV-c.<ori>

Such That:

ssss 4 Mnemonic of Sending Device rrrr 4 Mnemonic of Receiving Device

cccccccc 1-10 Control Field; Used for Routing within the Interface

-c -T TCIC Only

.<ori> 9 Agency's FBI assigned Originating Agency Identifier

Followed By:

.NIC/<nic> 10 NIC number. Number assigned by NCIC upon record entry.

Or

.LIC/
1-10 License Plate Number. If the license plate number exceeds ten characters, only the last ten

characters should be used.

Or / And

.VIN/<vin> 1-20 Vehicle Identification Number. Alphanumeric. Single zero only, run of zeros only, single

alphabetic only, all alphabetics only, or spaces cannot be used.

And optionally

.VMA/<vma> 2-24 Vehicle Make. Code as defined in the NCIC 2000 Code Manual.

.RSH/<rsh> 1 Related Search Hit. Must be either Y or N.

.HDN/<hdn> 1 H.E.A.T. Inquiry Indicator. Indicates if this transaction is a result of a stop due to the presence

of a H.E.A.T. Decal. Must be either Y or N.

LV -- Locate Vehicle

Message Structure:

{ssss}TCC#\$1N01rrrr ccccccccc.LV.<ori>

Such That:

ssss 4 Mnemonic of Sending Device rrrr 4 Mnemonic of Receiving Device

cccccccc 1-10 Control Field; Used for Routing within the Interface .<ori> 9 Agency's FBI assigned Originating Agency Identifier

Followed by one of the following:

.LIC/
 1-10 License Plate Number. If the license plate number exceeds ten characters, only the last ten

should be used.

.OCA/<oca> 1-20 Originating Case Number. The only valid special characters are the hyphen and the space.

Other

exceptions are described in the NCIC 2000 Operating Manual.

OR

.VIN/<vin> 1-20 Vehicle Identification Number. Alphanumeric. Single zero only, run of zeros only, single

all alphabetics only, or spaces cannot be used.

.OCA/<oca> 1-20 Originating Case Number. The only valid special characters are the hyphen and the space.

Other

exceptions are described in the NCIC 2000 Operating Manual.

Followed By:

.<dor> 8 Date of Recovery in YYYYMMDD format.

.<rca> 1-20 OCA of Recovering Agency.

Followed Optionally by:

. <rps></rps>	10-21	Reason for Person Record Removal. Must be a valid NCIC-assigned code. See the NCIC 2000 Operating Manual.
. <par></par>	1	Persons Armed. $1 = Yes$, $2 = No$, or $3 = Not$ available. Can be entered only if RPS is entered.
. <hit></hit>	1-2	Wanted / Missing Person Hit Results. See the NCIC 2000 Operating Manual for specific coding instructions.
. <npa></npa>	1-3	Number of Persons Apprehended. See the NCIC 2000 Operating Manual for specific coding instructions.
. <npf></npf>	1-20	Number of Missing Persons Found. See the NCIC 2000 Operating Manual for specific coding instructions.
. <vnp></vnp>	1-8	Value of Recovered Property. See the NCIC 2000 Operating Manual for specific coding instructions.
. <vor></vor>	1-8	Value of Other Recovered Property. See the NCIC 2000 Operating Manual for specific coding instructions.
. <vrc></vrc>	1-8	Value of Recovered Contraband. See the NCIC 2000 Operating Manual for specific coding
		instructions.
.HDN/ <hdn></hdn>	1	Heat Decal Indicator. Y or N

CV -- Clear Vehicle

Message Structure:

{ssss}TCC#\$1N01rrrr ccccccccc.CV.<ori>

Such That:

ssss 4 Mnemonic of Sending Device rrrr 4 Mnemonic of Receiving Device

ccccccccc 1-10 Control Field; Used for routing within the interface system .<ori> 9 Agency's FBI assigned Originating Agency Identifier

Followed by only one of the following:

.LIC/
 1-10 License Plate Number. If the license plate number exceeds ten characters, only the last ten

characters should be used.

.OCA/<oca> 1-20 Originating Case Number. The only valid special characters are the hyphen and the space.

Other exceptions are described in the NCIC 2000 Operating Manual.

OR

.VIN/<vin> 1-20 Vehicle Identification Number. Alphanumeric. Single zero only, run of zeros only, single

alphabetic only, all alphabetics only, or spaces cannot be used.

.OCA/<oca> 1-20 Originating Case Number. The only valid special characters are the hyphen and the space.

Other exceptions are described in the NCIC 2000 Operating Manual.

Followed Optionally By:

. <dcl> .<rri> .<rca></rca></rri></dcl>	8 9 1-20	Date of Clear in YYYYMMDD format. ORI of Recovering Agency. OCA of Recovering Agency.
. <rpp></rpp>	10-21	Reason for Property Record Removal. Must be a valid NCIC-assigned code. See the NCIC 2000 Operating Manual.
. <npa></npa>	1-3	Number of Persons Apprehended. See the NCIC 2000 Operating Manual for specific coding instructions.
. <npf></npf>	1-20	Number of Missing Persons Found. See the NCIC 2000 Operating Manual for specific coding instructions.
. <vnp></vnp>	1-8	Value of Recovered Property. See the NCIC 2000 Operating Manual for specific coding instructions.
. <vor></vor>	1-8	Value of Other Recovered Property. See the NCIC 2000 Operating Manual for specific coding instructions.
. <vrc></vrc>	1-8	Value of Recovered Contraband. See the NCIC 2000 Operating Manual for specific coding instructions.
.HDN/ <hdn></hdn>	1	Heat Decal Indicator. Y or N